

PRODUCT SHEET

Self-levelling timber decking support pads with height regulation - joists from 20mm to 100mm



Article:	Height:	In a box:
185J	40 - 56 [mm]	25 pcs.
185.1J	50 - 70 [mm]	25 pcs.
185.2J	70 - 110 [mm]	25 pcs.
185.3J	110 - 160 [mm]	25 pcs.
185.4J	150 - 210 [mm]	25 pcs.
185.41J	200 - 300 [mm]	25 pcs.
185.42J	300 - 400 [mm]	25 pcs.
185.43J	400 - 500 [mm]	25 pcs.
185.44J	500 - 600 [mm]	25 pcs.
185.45J	600 - 700 [mm]	25 pcs.
185.46J	700 - 800 [mm]	25 pcs.
185.47J	800 - 900 [mm]	25 pcs.
185.48J	900 - 1000 [mm]	25 pcs.

These supports can be placed directly on waterproofing (tar roofing, PCV foil, EPDM etc.)

BENEFITS:

- adjustable head provides automatic levelling surface from **0%** up to slope.
- fast and simple solution to construct aesthetic floor.
- easy access to any installation hidden under the floor.
- thanks to the smooth height adjustment, the support pads allow to remove the ground irregularities.
- high thermal isolation provided by space between raised surface and foundation.
- unique headpiece provides perfect fit to any joist width.
- possible to regulate height even after fixing joist to support pad.
- the lower part of the support pad has been designed in such a way that the water is removed directly on the waterproofing and the

creation of water puddles is avoided.

- very high scope of adjustment.

It's not possible to mix regulated pads with modular pads.

One support pad endures the pressure of **1100 kg** while assuming a **50%** value reduction in order to keep the safety standards

Price for single unit.